




小型軸承

單列球軸承



開放形



Z

附單面防塵蓋



ZZ

附兩面防塵蓋



RS

附單面接觸
密封蓋(橡膠)



2RS

附兩面接觸
密封蓋(橡膠)



RU

附單面非接觸
密封蓋(橡膠)



2RU

附兩面非接觸
密封蓋(橡膠)

軸 承 型 號	主 要 尺 寸 (mm)				基本額定負荷(kgf)		容 許 回 轉 數 (rpm)			重量 (g)
	d	D	B	r _s 最小	動負荷 C _e	靜負荷 C ₀	脂 潤 滑		油潤滑	
							開放形 Z, ZZ RU, 2RU	RS, 2RS	開放形 Z	
692	2	6	2.3	0.15	34	10	86000	—	100000	0.2
3	3	8	3	0.15	56	17	67000	—	79000	0.6
4	4	11	4	0.15	98	29	56000	—	67000	1.8
5	5	13	4	0.2	135	50	52000	—	61000	2.2
6	6	15	5	0.2	175	68	47000	24000	56000	3.9
7	7	17	5	0.3	165	72	44000	23000	51000	5.3
8	8	19	6	0.3	230	93	40000	22000	47000	7.2
9	9	20	6	0.3	250	110	37000	21000	43000	7.5
602	2	7	2.8	0.15	40	13	69000	—	82000	0.5
3	3	9	3	0.15	44	16	63000	—	74000	0.9
4	4	12	4	0.2	99	37	55000	—	65000	2.1
5	5	14	5	0.2	135	50	52000	27000	61000	3.5
6	6	17	6	0.3	200	75	45000	22000	53000	5.8
7	7	19	6	0.3	265	105	41000	22000	48000	7.6
8	8	22	7	0.3	335	140	36000	19000	42000	12
9	9	24	7	0.3	340	145	34000	19000	41000	15
623	3	10	4	0.15	65	23	56000	32000	67000	1.6
4	4	13	5	0.2	135	50	47000	25000	57000	2.9
5	5	16	5	0.3	175	68	43000	—	51000	5.0
6	6	19	6	0.3	265	105	37000	20000	45000	8.1
7	7	22	7	0.3	335	140	33000	18000	39000	13
8	8	24	8	0.3	340	145	30000	18000	36000	18
9	9	26	8	0.6	460	200	29000	17000	34000	20
633	3	13	5	0.2	135	50	47000	—	57000	3.0
4	4	16	5	0.3	175	68	43000	—	51000	5.3
5	5	19	6	0.3	265	105	37000	19000	45000	8.5
6	6	22	7	0.3	335	140	33000	17000	39000	13
7	7	26	9	0.3	460	200	28000	15000	33000	24
8	8	28	9	0.3	460	200	28000	16000	33000	29
9	9	30	10	0.6	610	270	25000	15000	30000	35