




6000 系 統 單列球軸承



開放形



60Z
附單面
防塵蓋



60ZZ
附兩面
防塵蓋



60RS
附單面接觸
橡膠密封蓋



60 2RS
附兩面接觸
橡膠密封蓋



60RU
附單面非接觸
橡膠密封蓋



60 2RU
附兩面非接觸
橡膠密封蓋

軸 承 型 號	主 要 尺 寸 (mm)				基本額定負荷(kgf)		容 許 回 轉 數 (rpm)			重 量 (kg)
	d	D	B	r _s 最小	動負荷 C _e	靜負荷 C ₀	脂 潤 滑		油潤滑	
							開放形 Z, ZZ RU, 2RU	RS, 2RS	開放形 Z	
6000	10	26	8	0.3	465	200	31000	18000	36000	0.019
1	12	28	8	0.3	520	245	27000	16000	32000	0.022
2	15	32	9	0.3	570	290	23000	14000	27000	0.030
3	17	35	10	0.3	610	335	21000	12000	25000	0.039
4	20	42	12	0.6	955	515	17000	10000	21000	0.069
5	25	47	12	0.6	1030	595	15000	9300	18000	0.080
6	30	55	13	1	1350	840	13000	7800	15000	0.116
7	35	62	14	1	1630	1050	11000	6700	13000	0.155
8	40	68	15	1	1710	1170	10000	6100	12000	0.192
9	45	75	16	1	2140	1540	9200	5500	11000	0.245
10	50	80	16	1	2220	1690	8400	5000	9900	0.261
11	55	90	18	1.1	2880	2170	7600	4500	8900	0.385
12	60	95	18	1.1	3000	2370	7100	4200	8400	0.415
13	65	100	18	1.1	3110	2570	6600	4000	7800	0.435
14	70	110	20	1.1	3880	3160	6100	3600	7200	0.602
15	75	115	20	1.1	4030	3420	5700	3400	6800	0.638
16	80	125	22	1.1	4860	4060	5300	3200	6300	0.850
17	85	130	22	1.1	5040	4400	5000	3000	5900	0.890
18	90	140	24	1.5	5930	5070	4700	2800	5600	1.16
19	95	145	24	1.5	6160	5500	4400	2700	5200	1.21
20	100	150	24	1.5	6130	5520	4300	2600	5100	1.25
21	105	160	26	2	7370	6710	4000	2400	4700	1.59
22	110	170	28	2	8360	7440	3800	2300	4500	1.96
24	120	180	28	2	8660	8080	3600	2100	4200	2.07
26	130	200	33	2	10800	10300	3200	1900	3800	3.16
28	140	210	33	2	11200	11100	3000	1800	3600	3.55
30	150	225	35	2.1	12800	12900	2800	1700	3300	4.22
32	160	240	38	2.1	13900	13800	2600	1500	3000	5.22
34	170	260	42	2.1	16400	16400	2400	—	2800	6.80
36	180	280	46	2.1	18500	19800	2200	—	2600	10.3