




6200 系 統

單列球軸承



開放形



62Z
附單面
防塵蓋



62ZZ
附兩面
防塵蓋



62RS
附單面接觸
橡膠密封蓋



62 2RS
附兩面接觸
橡膠密封蓋



62RU
附單面非接觸
橡膠密封蓋



62 2RU
附兩面非接觸
橡膠密封蓋

軸 承 型 號	主 要 尺 寸 (mm)				基本額定負荷(kgf)		容 許 回 轉 數 (rpm)			重 量 (kg)
	d	D	B	r _e 最小	動負荷 C _o	靜負荷 C _o	脂 潤 滑		油潤滑	
							開放形 Z, ZZ RU, 2RU	RS, 2RS	開放形 Z	
6200	10	30	9	0.6	520	245	24000	15000	29000	0.032
1	12	32	10	0.6	690	310	22000	13000	27000	0.037
2	15	35	11	0.6	780	380	20000	12000	24000	0.045
3	17	40	12	0.6	975	490	17000	10000	21000	0.065
4	20	47	14	1	1310	680	15000	8700	17000	0.106
5	25	52	15	1	1430	800	13000	7700	15000	0.128
6	30	62	16	1	1980	1150	11000	6400	13000	0.199
7	35	72	17	1.1	2620	1570	9200	5500	11000	0.288
8	40	80	18	1.1	2970	1820	8300	5000	10000	0.366
9	45	85	19	1.1	3330	2070	7700	4600	9200	0.407
10	50	90	20	1.1	3580	2370	7100	4200	8500	0.463
11	55	100	21	1.5	4420	3000	6300	3800	7600	0.607
12	60	110	22	1.5	5350	3690	5700	3400	6900	0.783
13	65	120	23	1.5	5840	4090	5400	3200	6400	0.99
14	70	125	24	1.5	6340	4490	5100	3100	6100	1.07
15	75	130	25	1.5	6880	4920	4800	2900	5800	1.18
16	80	140	26	2	7410	5400	4500	2700	5400	1.40
17	85	150	28	2	8560	6310	4200	2500	5000	1.79
18	90	160	30	2	9790	7300	3900	2400	4700	2.15
19	95	170	32	2.1	11100	8350	3700	2200	4400	2.62
20	100	180	34	2.1	12500	9490	3500	2100	4200	3.14
21	105	190	36	2.1	13600	10700	3300	2000	3900	3.70
22	110	200	38	2.1	14700	12000	3100	1800	3700	4.36
24	120	215	40	2.1	15800	13400	2900	1700	3400	5.15
26	130	230	40	3	17000	14900	2700	1600	3200	5.82
28	140	250	42	3	17000	15300	2400	1500	2900	7.45
30	150	270	45	3	18000	17100	2200	—	2700	9.41
32	160	290	48	3	18900	19000	2100	—	2500	14.3
34	170	310	52	4	21700	22800	1900	—	2300	17.5
36	180	320	52	4	23200	24600	1800	—	2200	18.3