




6300 系 統
單列球軸承



開放形



63Z
附單面
防塵蓋



63ZZ
附兩面
防塵蓋



63RS
附單面接觸
橡膠密封蓋



63 2RS
附兩面接觸
橡膠密封蓋



63RU
附單面非接觸
橡膠密封蓋



63 2RU
附兩面非接觸
橡膠密封蓋

軸 承 型 號	主 要 尺 寸 (mm)				基本額定負荷(kgf)		容 許 回 轉 數 (rpm)			重量 (kg)
	d	D	B	r _s 最小	動負荷 C _o	靜負荷 C _o	脂 潤 滑		油潤滑	
							開放形 Z, ZZ RU, 2RU	RS, 2RS	開放形 Z	
6300	10	35	11	0.6	825	350	22000	13000	27000	0.053
1	12	37	12	1	990	425	20000	12000	25000	0.060
2	15	42	13	1	1160	555	17000	10000	20000	0.082
3	17	47	14	1	1390	675	15000	9100	18000	0.115
4	20	52	15	1.1	1620	800	14000	8300	17000	0.144
5	25	62	17	1.1	2100	1150	11000	6700	13000	0.232
6	30	72	19	1.1	2720	1530	9600	5800	12000	0.346
7	35	80	21	1.5	3400	1960	8500	5100	10000	0.457
8	40	90	23	1.5	4150	2450	7700	4600	9200	0.633
9	45	100	25	1.5	4980	3010	6800	4100	8100	0.833
10	50	110	27	2	6320	3900	6100	3600	7300	1.07
11	55	120	29	2	7300	4580	5600	3300	6700	1.37
12	60	130	31	2.1	8350	5320	5200	3100	6200	1.70
13	65	140	33	2.1	9450	6110	4800	2900	5800	2.08
14	70	150	35	2.1	10600	6960	4500	2700	5400	2.52
15	75	160	37	2.1	11600	7870	4200	2500	5000	3.02
16	80	170	39	2.1	12500	8840	3900	2400	4700	3.59
17	85	180	41	3	13500	9870	3700	2200	4400	4.23
18	90	190	43	3	14500	10900	3500	2100	4200	4.91
19	95	200	45	3	15600	12100	3300	2000	4000	5.67
20	100	215	47	3	17700	14400	3000	1800	3600	7.00
21	105	225	49	3	18700	15700	2900	1800	3500	8.05
22	110	240	50	3	20900	18300	2700	1600	3200	9.54
24	120	260	55	3	21100	18800	2500	—	3000	12.5
26	130	280	58	4	23400	21800	2300	—	2700	15.10
28	140	300	62	4	25800	25100	2100	—	2500	19.40
30	150	320	65	4	28000	29000	1900	—	2300	26.2
32	160	340	68	4	28300	29200	1800	—	2200	29.0