


6800 系 統
單列球軸承



軸 承 型 號	主 要 尺 寸 (mm)				基本額定負荷(kgf)		容 許 回 轉 數 (rpm)			重量 (kg)
	d	D	B	r _s 最小	動負荷 C _e	靜負荷 C ₀	脂 潤 滑		油潤滑	
							開放形 Z, ZZ RU, 2RU	RS, 2RS	開放形 Z	
6800	10	19	5	0.3	175	86	37000	—	43000	0.005
1	12	21	5	0.3	195	105	33000	—	39000	0.006
2	15	24	5	0.3	210	130	28000	—	33000	0.007
3	17	26	5	0.3	265	160	26000	—	30000	0.008
4	20	32	7	0.3	410	250	21000	—	25000	0.018
5	25	37	7	0.3	440	300	18000	—	21000	0.022
6	30	42	7	0.3	460	350	15000	—	18000	0.026
7	35	47	7	0.3	485	390	13000	—	16000	0.030
8	40	52	7	0.3	505	425	12000	—	14000	0.033
9	45	58	7	0.3	630	550	11000	—	13000	0.040
10	50	65	7	0.3	670	620	9600	—	11000	0.052
11	55	72	9	0.3	895	825	8700	—	10000	0.083
12	60	78	10	0.3	1170	1080	8000	—	9400	0.104
13	65	85	10	0.6	1220	1170	7300	—	8600	0.126
14	70	90	10	0.6	1230	1220	6800	—	8100	0.134
15	75	95	10	0.6	1280	1310	6400	—	7600	0.142
16	80	100	10	0.6	1290	1360	6100	—	7200	0.150
17	85	110	13	1	1910	1940	5600	—	6600	0.266
18	90	115	13	1	1940	2010	5300	—	6300	0.279
20	100	125	13	1	1990	2160	4800	—	5700	0.309
22	110	140	16	1	2860	3130	4300	—	5100	0.606
24	120	150	16	1	2950	3360	4000	—	4700	0.655
26	130	165	18	1.1	3760	4200	3600	—	4300	0.939
28	140	175	18	1.1	3900	4530	3400	—	4000	1.00
30	150	190	20	1.1	4870	5600	3100	—	3700	1.40
32	160	200	20	1.1	4930	5800	2900	—	3400	1.45