




7000 系統 (接觸角 30°)
向心止推球軸承



軸 承 型 號	主 要 尺 寸 (mm)					基本額定負荷 (kgf)		容許回轉數(rpm)		重量 (kg)
	d	D	B	r _s 最小	r _{1s} 最小	動負荷 C _e	靜負荷 C _o	脂潤滑	油潤滑	
7002	15	32	9	0.3	0.15	625	350	21000	26000	0.035
03	17	35	10	0.3	0.15	780	510	19000	23000	0.045
04	20	42	12	0.6	0.3	1050	620	16000	19000	0.079
05	25	47	12	0.6	0.3	1150	750	14000	17000	0.091
7006	30	55	13	1	0.6	1480	1030	12000	14000	0.133
07	35	62	14	1	0.6	1780	1280	10000	12000	0.17
08	40	68	15	1	0.6	1910	1490	9300	11000	0.21
09	45	75	16	1	0.6	2270	1800	8300	10000	0.26
7010	50	80	16	1	0.6	2410	2050	7700	9200	0.29
11	55	90	18	1.1	0.6	3170	2680	6900	8300	0.42
12	60	95	18	1.1	0.6	3250	2860	6400	7700	0.45
13	65	100	18	1.1	0.6	3430	3200	6000	7200	0.47
7014	70	110	20	1.1	0.6	4350	4010	5500	6600	0.66
15	75	115	20	1.1	0.6	4450	4250	5200	6300	0.69
16	80	125	22	1.1	0.6	5440	5160	4800	5800	0.93
17	85	130	22	1.1	0.6	5560	5470	4600	5500	0.97
7018	90	140	24	1.5	1	6650	6450	4300	5100	1.26
19	95	145	24	1.5	1	6790	6840	4000	4800	1.32
20	100	150	24	1.5	1	6970	7190	3900	4700	1.37
21	105	160	26	2	1	8130	8350	3600	4400	1.73
7022	110	170	28	2	1	9370	9460	3500	4200	2.14
24	120	180	28	2	1	9850	10500	3200	3900	2.27
26	130	200	33	2	1	11900	12800	2900	3500	3.43
28	140	210	33	2	1	12200	13500	2700	3300	3.64
7030	150	225	35	2.1	1.1	13900	15700	2500	3000	4.43
32	160	240	38	2.1	1.1	15800	18000	2400	2800	4.45