




7000C 系統 (接觸角 15°)
向心止推球軸承



軸 承 型 號	主 要 尺 寸 (mm)					基本額定負荷 (kgf)		容許回轉數(rpm)		重量 (kg)
	d	D	B	r_s 最小	r_{1s} 最小	動負荷 C_o	靜負荷 C_o	脂潤滑	油潤滑	
7002C	15	32	9	0.3	0.15	675	375	32000	43000	0.035
03C	17	35	10	0.3	0.15	745	455	28000	38000	0.045
04C	20	42	12	0.6	0.3	1130	670	24000	32000	0.079
05C	25	47	12	0.6	0.3	1250	815	21000	28000	0.091
7006C	30	55	13	1	0.6	1620	1120	18000	24000	0.133
07C	35	62	14	1	0.6	1950	1400	15000	21000	0.17
08C	40	68	15	1	0.6	2090	1620	14000	19000	0.21
09C	45	75	16	1	0.6	2490	1960	12000	17000	0.26
7010C	50	80	16	1	0.6	2650	2240	12000	15000	0.29
11C	55	90	18	1.1	0.6	3480	2920	10000	14000	0.42
12C	60	95	18	1.1	0.6	3570	3120	9600	13000	0.45
13C	65	100	18	1.1	0.6	3780	3500	9000	12000	0.47
7014C	70	110	20	1.1	0.6	4780	4380	8300	11000	0.66
15C	75	115	20	1.1	0.6	4900	4650	7800	10000	0.69
16C	80	125	22	1.1	0.6	5980	5640	7200	9700	0.93
17C	85	130	22	1.1	0.6	6120	5990	6800	9100	0.97
7018C	90	140	24	1.5	1	7310	7050	6400	8600	1.26
19C	95	145	24	1.5	1	7480	7480	6000	8100	1.32
20C	100	150	24	1.5	1	7680	7880	5900	7900	1.37
21C	105	160	26	2	1	8950	9140	5500	7300	1.73
7022C	110	170	28	2	1	10300	10300	5200	7000	2.14
24C	120	180	28	2	1	10900	11500	4900	6500	2.27
26C	130	200	33	2	1	13200	14000	4400	5800	3.43
28C	140	210	33	2	1	13400	14800	4100	5500	3.64
7030C	150	225	35	2.1	1.1	15400	17200	3800	5000	4.43
32C	160	240	38	2.1	1.1	17400	19700	3500	4700	5.45