


7200 系統 (接觸角 30°)

向心止推球軸承



軸 承 型 號	主 要 尺 寸 (mm)					基本額定負荷 (kgf)		容許回轉數 (rpm)		重量 (kg)
	d	D	B	r _a 最小	r _{1a} 最小	動負荷 C _e	靜負荷 C ₀	脂潤滑	油潤滑	
7202	15	35	11	0.6	0.3	825	435	20000	24000	0.048
03	17	40	12	0.6	0.3	1040	560	17000	21000	0.070
04	20	47	14	1	0.6	1480	855	15000	17000	0.112
05	25	52	15	1	0.6	1560	970	13000	15000	0.135
7206	30	62	16	1	0.6	2180	1390	11000	13000	0.208
07	35	72	17	1.1	0.6	2870	1900	9200	11000	0.295
08	40	80	18	1.1	0.6	3430	2380	8300	10000	0.382
09	45	85	19	1.1	0.6	3850	2710	7800	9300	0.430
7210	50	90	20	1.1	0.6	4020	2990	7100	8500	0.485
11	55	100	21	1.5	1	4960	3790	6300	7600	0.635
12	60	110	22	1.5	1	6010	4660	5700	6900	0.82
13	65	120	23	1.5	1	6860	5520	5400	6400	1.02
7214	70	125	24	1.5	1	7120	5670	5100	6100	1.12
15	75	130	25	1.5	1	8080	6650	4800	5800	1.23
16	80	140	26	2	1	8700	7290	4500	5400	1.50
17	85	150	28	2	1	10100	8520	4200	5000	1.87
7218	90	160	30	2	1	11500	9860	3900	4700	2.30
19	95	170	32	2.1	1.1	12400	10500	3700	4400	2.78
20	100	180	34	2.1	1.1	14000	12000	3500	4100	3.32
21	105	190	36	2.1	1.1	15200	13500	3300	3900	3.95
7222	110	200	38	2.1	1.1	16500	15100	3100	3700	4.65
24	120	215	40	2.1	1.1	17800	16900	2900	3400	5.49
26	130	230	40	3	1.1	20000	20200	2700	3200	6.21
28	140	250	42	3	1.1	22300	23900	2400	2900	7.76
7230	150	270	45	3	1.1	25300	28500	2200	2700	9.75
32	160	290	48	3	1.1	23500	26800	2100	2500	12.1