




7200B 系統 (接觸角 40°)

向心止推球軸承



軸 承 型 號	主 要 尺 寸 (mm)					基本額定負荷 (kgf)		容許回轉數(rpm)		重量 (kg)
	d	D	B	r_s 最小	r_{1s} 最小	動負荷 C_o	靜負荷 C_o	脂潤滑	油潤滑	
7202B	15	35	11	0.6	0.3	755	400	16000	22000	0.048
03B	17	40	12	0.6	0.3	950	515	14000	19000	0.070
04B	20	47	14	1	0.6	1360	785	12000	16000	0.112
05B	25	52	15	1	0.6	1430	885	10000	14000	0.135
7206B	30	62	16	1	0.6	1980	1280	8600	12000	0.208
07B	35	72	17	1.1	0.6	2610	1740	7300	10000	0.295
08B	40	80	18	1.1	0.6	3120	2180	6700	9200	0.382
09B	45	85	19	1.1	0.6	3500	2480	6200	8600	0.430
7210B	50	90	20	1.1	0.6	3640	2730	5700	7800	0.485
11B	55	100	21	1.5	1	4500	3450	5000	6900	0.635
12B	60	110	22	1.5	1	5450	4250	4600	6300	0.82
13B	65	120	23	1.5	1	6210	5030	4300	5900	1.02
7214B	70	125	24	1.5	1	6450	5160	4100	5600	1.12
15B	75	130	25	1.5	1	7310	6050	3900	5300	1.23
16B	80	140	26	2	1	7860	6630	3600	4900	1.50
17B	85	150	28	2	1	9090	7750	3400	4600	1.87
7218B	90	160	30	2	1	10400	8970	3100	4300	2.30
19B	95	170	32	2.1	1.1	11300	9590	3000	4100	2.78
20B	100	180	34	2.1	1.1	12700	10900	2800	3800	3.32
21B	105	190	36	2.1	1.1	13800	12300	2600	3600	3.95
7222B	110	200	38	2.1	1.1	15000	13800	2500	3400	4.65
24B	120	215	40	2.1	1.1	16100	15400	2300	3200	5.49
26B	130	230	40	3	1.1	18100	18300	2100	2900	6.21
28B	140	250	42	3	1.1	20100	21700	1900	2700	7.76
7230B	150	270	45	3	1.1	22900	25900	1800	2400	9.75
32B	160	290	48	3	1.1	24200	28400	1600	2300	12.1