


7300B 系統（接觸角 40°）

向心止推球軸承



軸 承 型 號	主 要 尺 寸 (mm)					基本額定負荷 (kgf)		容許回轉數(rpm)		重量 (kg)
	d	D	B	r_s 最小	r_{1s} 最小	動負荷 C_e	靜負荷 C_o	脂潤滑	油潤滑	
7303B	17	47	14	1	0.6	1410	745	12000	17000	0.120
04B	20	52	15	1.1	0.6	1650	885	11000	15000	0.150
05B	25	62	17	1.1	0.6	2330	1360	9200	13000	0.243
06B	30	72	19	1.1	0.6	2820	1770	7700	11000	0.362
7307B	35	80	21	1.5	1	3310	2060	6800	9400	0.475
08B	40	90	23	1.5	1	4050	2570	6100	8400	0.675
09B	45	100	25	1.5	1	5160	3470	5500	7500	0.875
10B	50	110	27	2	1	6560	4520	4900	6700	1.14
7311B	55	120	29	2	1	7580	5300	4500	6100	1.45
12B	60	130	31	2.1	1.1	8660	6150	4100	5700	1.81
13B	65	140	33	2.1	1.1	9800	7070	3800	5300	2.22
14B	70	150	35	2.1	1.1	11000	8040	3600	4900	2.70
7315B	75	160	37	2.1	1.1	12000	9090	3400	4600	3.15
16B	80	170	39	2.1	1.1	13000	10200	3100	4300	3.85
17B	85	180	41	3	1.1	14000	11400	3000	4100	4.53
18B	90	190	43	3	1.1	15000	12600	2800	3800	5.30
7319B	95	200	45	3	1.1	16100	13900	2600	3600	6.12
20B	100	215	47	3	1.1	17200	15100	2400	3300	7.53
21B	105	225	49	3	1.1	19400	18100	2300	3200	8.62
22B	110	240	50	3	1.1	21700	21200	2100	3000	10.1
7324B	120	260	55	3	1.1	23000	23600	2000	2700	12.6
26B	130	280	58	4	1.5	25500	27400	1800	2500	15.4
28B	140	300	62	4	1.5	30800	35100	1700	2300	18.8
30B	150	320	65	4	1.5	32400	38700	1600	2100	22.4
7332B	160	340	68	4	1.5	33900	42400	1400	2000	26.4
34B	170	360	72	4	1.5	36200	45300	1300	1900	31.2