




7300C 系統（接觸角 15°）

向心止推球軸承



軸 承 型 號	主 要 尺 寸 (mm)					基本額定負荷 (kgf)		容許回轉數 (rpm)		重量 (kg)
	d	D	B	r _s 最小	r _{1s} 最小	動負荷 C _e	靜負荷 C _o	脂潤滑	油潤滑	
7303C	17	47	14	1	0.6	1610	885	23000	30000	0.120
04C	20	52	15	1.1	0.6	1890	1020	21000	28000	0.150
05C	25	62	17	1.1	0.6	2690	1560	17000	23000	0.243
06C	30	72	19	1.1	0.6	3290	2060	14000	19000	0.362
7307C	35	80	21	1.5	1	3870	2400	13000	17000	0.475
08C	40	90	23	1.5	1	4720	3000	12000	15000	1.675
09C	45	100	25	1.5	1	6030	4050	10000	14000	0.875
10C	50	110	27	2	1	7660	5260	9100	12000	1.14
7311C	55	120	29	2	1	8850	6170	8400	11000	1.45
12C	60	130	31	2.1	1.1	10100	7170	7700	10000	1.81
13C	65	140	33	2.1	1.1	11400	8230	7200	9600	2.22
14C	70	150	35	2.1	1.1	12900	9370	6700	9000	2.70
7315C	75	160	37	2.1	1.1	14000	10600	6300	8400	3.15
16C	80	170	39	2.1	1.1	15200	11900	5900	7900	3.85
17C	85	180	41	3	1.1	16400	13300	5500	7400	4.53
18C	90	190	43	3	1.1	17600	14700	5200	7000	5.30
7319C	95	200	45	3	1.1	18900	16300	4900	6600	6.12
20C	100	215	47	3	1.1	20100	17600	4600	6100	7.53
21C	105	225	49	3	1.1	22700	21100	4400	5800	8.62
22C	110	240	50	3	1.1	25400	24700	4000	5400	10.1