





21300RH 系統

球面滾柱軸承



213
圓柱孔



213K
圓錐孔
錐度 1 : 12

軸 承 號		主 要 尺 寸 (mm)				基本額定負荷 (kgf)		容許回轉數 (rpm)		重 量 (kg)	
圓柱孔	圓錐孔	d	D	B	r _s 最小	動負荷 C _e	靜負荷 C ₀	脂潤滑	油潤滑	213R	213RK
21308RH	21308RHK	40	90	23	1.5	8510	9230	4500	6100	0.71	0.699
09RH	09RHK	45	100	25	1.5	10600	11900	4000	5400	0.95	0.935
10RH	10RHK	50	110	27	2	13100	15300	3700	4900	1.21	1.19
11RH	11RHK	55	120	29	2	14700	16900	3000	4100	1.58	1.56
21312RH	21312RHK	60	130	31	2.1	17200	19700	2800	3700	1.96	1.93
13RH	13RHK	65	140	33	2.1	19800	23700	2600	3400	2.45	2.41
14RH	14RHK	70	150	35	2.1	21900	26500	2400	3200	2.99	2.95
15RH	15RHK	75	160	37	2.1	25000	30400	2200	3000	3.56	3.51
21316RH	21316RHK	80	170	39	2.1	28100	34600	2100	2800	4.18	4.12
17RH	17RHK	85	180	41	3	30600	38000	2000	2600	4.98	4.91
18RH	18RHK	90	190	43	3	33700	42400	1900	2500	5.80	5.71
19RH	19RHK	95	200	45	3	36900	47000	1800	2300	7.15	7.05
21320RH	21320RHK	100	215	47	3	42400	53500	1600	2200	8.79	8.67
22RH	22RHK	110	240	50	3	49300	62900	1400	1900	11.8	11.6