





51200,53200,53200U 系統


單向推力球軸承



512



532



532U

軸 承 型 號			主 要						
512	532	532U	d	d _e	d _u	D	D _u	H	H _s
51200	53200	53200U	10	12	18	26	28	11	11.6
01	01	01U	12	14	20	28	30	11	11.4
02	02	02U	15	17	24	32	35	12	13.3
03	03	03U	17	19	26	35	38	12	13.2
51204	53204	53204U	20	22	30	40	42	14	14.7
05	05	05U	25	27	36	47	50	15	16.7
06	06	06U	30	32	42	52	55	16	17.8
07	07	07U	35	37	48	62	68	18	19.9
51208	53208	53208U	40	42	55	68	72	19	20.3
09	09	09U	45	47	60	73	78	20	21.3
10	10	10U	50	52	62	78	82	22	23.5
11	11	11U	55	57	72	90	95	25	27.3
51212	53212	53212U	60	62	78	95	100	26	28
13	13	13U	65	67	82	100	105	27	28.7
14	14	14U	70	72	88	105	110	27	28.8
15	15	15U	75	77	92	110	115	27	28.3
51216	53216	53216U	80	82	98	115	120	28	29.5
17	17	17U	85	88	105	125	130	31	33.1
18	18	18U	90	93	110	135	140	35	38.5
20	20	20U	100	103	125	150	155	38	40.9
51222	53222	53222U	110	113	135	160	165	38	40.2
24	24	24U	120	123	145	170	175	39	40.8
26	26	26U	130	133	160	190	195	45	47.9
28	28	28U	140	143	170	200	210	46	48.6
51230	53230	53230U	150	153	180	215	225	50	53.3
32	32	32U	160	163	190	225	235	51	54.7
34	34	34U	170	173	200	240	250	55	58.7
36	36	36U	180	183	210	250	260	56	58.2
51238	53238	53238U	190	194	230	270	280	62	65.7
40	40	40U	200	204	240	280	290	62	65.3
44	44	44U	220	224	260	300	310	63	65.6
48	48	48U	240	244	290	340	350	78	81.6
52	52	52U	260	264	305	360	370	79	82.8

尺 寸 (mm)					基本額定負荷 (kgf)		重 量 (kg)		
H _u	A	R _s	S _u	r _s 最小	動負荷 C _e	靜負荷 C _o	512	532	532U
13	8.5	22	3.5	0.6	1290	1740	0.030	0.029	0.037
13	11.5	25	3.5	0.6	1340	1940	0.034	0.031	0.043
15	12	28	4	0.6	1690	2530	0.046	0.048	0.062
15	16	32	4	0.6	1750	2780	0.053	0.055	0.070
17	18	36	5	0.6	2270	3840	0.082	0.080	0.100
19	19	40	5.5	0.6	2820	5140	0.12	0.12	0.152
20	22	45	5.5	0.6	2860	5540	0.15	0.16	0.193
22	24	50	7	1	4150	8540	0.22	0.22	0.277
23	28.5	56	7	1	4780	10000	0.27	0.27	0.340
24	26	56	7.5	1	4870	10700	0.32	0.31	0.397
26	32.5	64	7.5	1	4950	11400	0.39	0.38	0.48
30	35	72	9	1	7070	16200	0.61	0.62	0.77
31	32.5	72	9	1	7500	18200	0.69	0.69	0.85
32	40	80	9	1	7630	19200	0.77	0.75	0.93
32	38	80	9	1	7500	19200	0.81	0.80	0.99
32	49	90	9.5	1	7890	21300	0.86	0.85	1.06
33	46	90	10	1	8010	22300	0.95	0.93	1.15
37	52	100	11	1	9410	25600	1.29	1.28	1.57
42	45	100	13.5	1.1	11900	33200	1.77	1.77	2.19
45	52	112	14	1.1	14900	41800	2.36	2.34	2.84
45	65	125	14	1.1	15100	43900	2.57	2.50	3.06
46	61	125	15	1.1	15700	48100	2.86	2.81	3.46
53	67	140	17	1.5	20700	63400	4.19	4.08	4.98
55	87	160	17	1.5	21900	68200	4.57	4.46	5.98
60	79	160	20.5	1.5	24800	78300	5.77	5.58	7.27
61	74	160	21	1.5	25200	81900	6.67	6.23	8.04
65	91	180	21.5	1.5	27500	89100	8.28	7.85	9.99
66	112	200	21.5	1.5	30000	101000	8.85	8.25	10.6
73	98	200	23	2	30400	103000	11.9	11.4	14.1
74	125	225	23	2	32000	113000	12.4	11.8	15.0
75	118	225	25	2	34900	133000	13.7	12.8	16.1
92	122	250	30	2.1	45100	184000	23.6	21.4	26.1
93	152	280	30	2.1	45400	191000	25.6	23.2	29.1