






51300,53300,53300U 系統
單向推力球軸承



513



533



533U

軸 承 型 號			主 要						
513	533	533U	d	d _e	d _u	D	D _u	H	H _s
51305	53305	53305U	25	27	38	52	55	18	19.8
06	06	06U	30	32	45	60	62	21	22.6
07	07	07U	35	37	52	68	72	24	25.6
08	08	08U	40	42	60	78	82	26	28.5
51309	53309	53309U	45	47	65	85	90	28	30.1
10	10	10U	50	52	72	95	100	31	34.3
11	11	11U	55	57	80	105	110	35	39.3
12	12	12U	60	62	85	110	115	35	38.3
51313	53313	53313U	65	67	90	115	120	36	39.4
14	14	14U	70	72	98	125	130	40	44.2
15	15	15U	75	77	105	135	140	44	48.1
16	16	16U	80	82	110	140	145	44	47.6
51317	53317	53317U	85	88	115	150	155	49	53.1
18	18	18U	90	93	120	155	160	50	54.6
20	20	20U	100	103	135	170	175	55	59.2
22	22	22U	110	113	150	190	195	63	67.2
51324	53324	53324U	120	123	165	210	220	70	74.1
26	26	26U	130	134	177	225	235	75	80.3
28	28	28U	140	144	190	240	250	80	84.9
30	30	30U	150	154	200	250	260	80	83.7
51332	53332	53332U	160	164	215	270	280	87	91.7
34	34	34U	170	174	220	280	290	87	91.3
36	36	36U	180	184	240	300	310	95	99.3
38	38	38U	190	195	255	320	330	105	111
40	40	40U	200	205	270	340	350	110	118.4

尺 寸 (mm)					基本額定負荷 (kgf)		重 量 (kg)		
H _U	A	R _s	S _U	r _s 最小	動負荷 C _e	靜負荷 C _o	513	533	533U
22	21	45	6	1	3640	6270	0.18	0.18	0.224
25	22	50	7	1	4360	8020	0.27	0.27	0.326
28	24	56	7.5	1	5660	10700	0.39	0.40	0.484
31	28	64	8.5	1	7060	13700	0.55	0.57	0.69
33	25	64	10	1	8160	16700	0.69	0.68	0.85
37	28	72	11	1.1	9340	19000	1.00	1.01	1.24
42	30	80	11.5	1.1	12200	25100	1.34	1.41	1.69
42	41	90	11.5	1.1	12600	27200	1.43	1.47	1.78
43	38.5	90	12.5	1.1	13000	29300	1.57	1.61	1.95
48	43	100	13	1.1	15100	34600	2.06	2.15	2.56
52	37	100	15	1.5	17400	40400	2.68	2.72	3.27
52	50	112	15	1.5	18000	43300	2.82	2.86	3.43
58	43	112	17.5	1.5	21000	49800	3.66	3.63	4.44
59	40	112	18	1.5	21700	53400	3.88	3.87	4.71
64	46	125	18	1.5	24100	60800	5.11	5.10	6.05
72	51	140	20.5	2	28500	76900	7.87	7.78	9.05
80	63	160	22	2.1	33200	94900	10.9	10.7	12.7
86	53	160	26	2.1	35300	105000	13.3	13.0	15.5
92	68	180	26	2.1	37400	115000	15.9	15.5	18.4
92	89.5	200	26	2.1	38400	123000	16.7	16.1	19.2
100	77	200	29	3	47900	160000	21.5	21.5	23.9
100	105	225	29	3	47200	160000	22.5	22.5	25.0
109	91	225	32	3	47200	161000	28.7	27.5	30.5
121	104	250	33	4	55400	199000	36.7	37.0	40.4
130	92	250	38	4	60800	227000	43.7	43.5	47.5